

RJ45 JACK R/A PCB T/H UNSHIELDED



MATERIAL

Insulator: Thermoplastic UL94V-0

Contact: Phosphor Bronze

Plated: Gold Plated over Nickel in contact

Tin plated over Nickel in solder area

ELECTRICAL

Voltage Rating: 125 Vac Rms.

Current Rating: 1.5 Amp.

ENVIRONMENTAL:







Storage: -40°C To +85°C.

Operation: -20°C To +75°C.


MECHANICAL:

Operating: 750 Cycles Min.

243




PCB LAYOUT/TOP VIEW



PCB LAYOUT/TOP VIEW

RJ45 JACK R/A PCB T/H SHIELDED



MATERIAL

Insulator: Thermoplastic UL94V-0

Contact: Phosphor Bronze

Plated: Gold Plated over Nickel in contact

Tin plated over Nickel in solder area

Shielded: Brass with Nickel plated

ELECTRICAL

Voltage Rating: 125 Vac Rms.

Current Rating: 1.5 Amp.

ENVIRONMENTAL:







Storage: -40°C To +85°C.

Operation: -20°C To +75°C.



MECHANICAL:

Operating: 750 Cycles Min.

243



PCB LAYOUT/TOP VIEW



PCB LAYOUT/TOP VIEW